

Model:RS-M8XTX磁钢加大
20 CM Mid-Range Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	208x96.6	mm
Nominal Power Handling	175	W
Maximum Power	400	W
Sensitivity	96	db
Frequency Response	100-12000	Hz
Cone Material	Non Pressed Paper Cone	
Basket	Aluminium	
Net Weight	3.2	kg
Electrical Data		
Nominal Impedance	4	ohm
DC Resistance	3	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	38.6	mm
Voice Coil Height	7.5	mm
HE magnetic Gap Height	6	mm
Voice Coil bobbin	TIL	
Number of Layers	2L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	0.24	Cms
Mechanical Q Factor	4.07	Qms
Electrical Q Factor	0.52	Qes
Total Q Factor	0.46	Qts
Moving Mass	12.8	Mms
Eq.Cas AIR Load	17.5	Vas
Resonant Frequency	91	Fs
Effective Piston Area	227cm ²	SD

FEATURES

- * Aluminium Basket
- * Non Pressed Paper Cone With Treated Choth Surround
- * High Temperature 1.5" CCAW Voice Coil
- * Ferrite Magnet Structre

Dimensions

